

ValueBond PX Filter Cartridges

Polyester meltblown depth filter for process fluid applications

The ValueBond PX (Polyester) cartridges are polyester thermally bonded filters manufactured with no resins, binders, or adhesives. Their multi-depth layer construction makes them ideal for high dirt-holding and long service life within many process fluid applications.

Available in nominal ratings of 1, 3, 5, 10, 25, 50, 75, and 100 micron.



Contact Information

Parker-Hannifin Corporation
Bioscience & Water Filtration Division
2340 Eastman Avenue
Oxnard, California, USA 93030

toll free +1 877 784 2234
phone +1 805 604 3400
bwf.oxn.support@support.parker.com

www.parker.com/bioscience

Features & Benefits

- Rigid polyester core
- Thermally bonded melt blown fiber matrix provides dimensionally stable construction
- Rated temperature up to 250°F
- Multi-depth layer structure delivers high-dirt-holding capacity
- Design is optimized to provide high-flow rates, low ΔP , and reduced operating costs
- Polyester construction provides broad chemical compatibility for a variety of process applications

Applications

- Bulk Oil
- Can Coolant
- Chemical Processing
- DI Water
- Edible Oil
- Paints & Coatings
- Plating Solutions
- Organic Solvents



ENGINEERING YOUR SUCCESS.

