



MATRIKX + CTO[®]/2

Extruded Activated Carbon Block Filter

The Workhorse

- **5 µm Nominal Filtration**
- **High Adsorptive Capacity and Efficiency**
- **Efficient Sediment Filter**
- **No Release of Carbon Fines**
- **Competitively Priced vs. GAC filters**
- **Performance Tested and Verified by Independent Laboratory Testing**



MATRIKX + CTO[®]/2 filters are the most widely used carbon block devices in the world and provide previously unattainable performance at the lowest price point. MATRIKX + CTO[®]/2 filters simultaneously remove free chlorine and organic chemicals that contribute to taste and odor while providing the particulate filtration and dirt-holding capacity of an efficient 5 µm nominal sediment filter. These filters are optimized for applications where they perform the role of both a sediment and activated carbon filter.

The extrusion process allows the production of a carbon block with more carbon, but a lower pressure drop. This enables a MATRIKX + CTO[®]/2 filter to deliver extended life while removing sediment, chlorine, taste, odor and organic contaminants from water, aqueous solutions or suspensions. The MATRIKX + CTO[®]/2 is also widely used in filtering organic solvents. The MATRIKX + CTO[®]/2 is ideal for use in residential and commercial water purification systems, food service, pre- and post-RO systems.

MATRIKX + CTO[®]/2 or GAC?

The MATRIKX + CTO[®]/2 is manufactured from high purity acid-washed activated carbon. Its dirt-holding capacity and the absence of carbon fines makes the MATRIKX + CTO[®]/2 the filter of choice. A superior carbon block, MATRIKX + CTO[®]/2 combines both high performance and integrity with an exceptional cost-to-performance value. As a result, MATRIKX + CTO[®]/2 virtually renders GAC filters obsolete by comparison.

Technical Specifications and Order Information

Part No.	O.D. x Length	Weight	Chlorine Capacity @ Flow	Nominal µm Rating	Initial ΔP @ Flow
32-250-125-975	2.50" x 9.75"	0.75 lbs.	>6,000 gal. @ 1.0 GPM	5 µm	2.0 psid @ 1.0 GPM
32-250-125-20	2.50" x 20"	1.75 lbs.	>12,000 gal. @ 2.0 GPM	5 µm	2.0 psid @ 2.0 GPM
32-425-125-975	4.25" x 9.75"	2.60 lbs.	>12,000 gal. @ 3.0 GPM	5 µm	4.0 psid @ 3.5 GPM
32-425-125-20	4.25" x 20"	5.60 lbs.	>26,000 gal. @ 7.0 GPM	5 µm	4.5 psid @ 7.0 GPM



"Quality to the Core"

ORDER INFORMATION

Special order filters are available in varying sizes with lengths from 1" to 60".

Standard filters are finished with an outer polypropylene spunbonded prefiltration medium. A protective polypropylene netting is applied to the exterior of the cartridge. Polypropylene end caps with compression gaskets fit most standard housings.

Inquire concerning alternative filter finishing options, including alternative end cap and housing interface styles, a wide range of non-standard extruded filter sizes, and non-standard prefiltration systems.

EXTRUDED CARBON = EXCEPTIONAL VALUE

MATRIKX + CTO[®]/2 filters consist of activated carbon particles fused into a uniform block with enhanced adsorptive capacity and efficiency. MATRIKX + CTO[®]/2 filters flow in a radial (outside-to-inside) direction, providing increased dirt-holding capacity and low pressure drop. Unlike granular activated carbon (GAC) filters, MATRIKX + CTO[®]/2 cartridges will not channel or bypass, due to the extreme uniformity of their extruded activated carbon core. Service life of the MATRIKX + CTO[®]/2 filter is greatly extended by a layer of 1.5 µm polypropylene spunbonded prefiltration medium.

- No channeling
- No fluidizing
- No bypassing
- Eliminates release of carbon fines
- Lowest extractables, pure materials of construction
- Maximum service life and resistance to fouling
- Manufactured using FDA-compliant materials

Made in the USA.

Distributed by:



NOTES

1. Performance of a given MATRIKX[®] extruded carbon filter varies in direct proportion to the total weight of carbon in each filter.
2. Projected chlorine reduction capacity when tested in accordance with NSF/ANSI Standard 42 protocol for chlorine reduction.
3. Nominal particulate rating (5 µm) is for >85% of a given size as determined from single-pass particle counting results.*
4. Absolute particulate rating (10 µm) is for >99.9% of particles of a given size as determined from single-pass particle counting results.**
5. Actual results obtained will vary with various combinations of organic contaminants, changes in pH or other conditions encountered in actual use.
6. All information presented here is based on data believed to be reliable. It is offered for evaluation and verification, but is not to be considered a warranty of any kind.
7. MATRIKX + CTO[®]/2 filters are designed to fit most standard household and commercial or industrial housings.
8. Contact KX Industries, L.P. to check filter housing compatibility.
9. This cartridge must be placed in an appropriate housing and flushed for a minimum of 10 minutes prior to use.

* Nominal Filter Rating: Filter rating indicating the approximate size particle, the majority of which will not pass through the filter. It is generally interpreted as meaning that 85% of the particles of the size equal to the nominal micron rating will be retained by the filter. (WQA Glossary of Terms, Third Edition, 3-97).

** Absolute Filter Rating: Filter rating meaning that 99.9% (or essentially all) of the particles larger than a specific micron rating will be trapped on or within the filter. (WQA Glossary of Terms, Third Edition, 3-97).

WARNINGS:

Maximum Operating Temperature:	125°F
Maximum Operating Pressure:	250 psig
Maximum Differential Pressure:	100 psid
Collapse Pressure:	200 psid

MATRIKX + CTO[®]/2 filters are not to be autoclaved or steam-sterilized.

Use MATRIKX + CTO[®]/2 carbon filters only with microbiologically safe and adequately disinfected water.

LIMITED LIABILITY

KX Industries, L.P. makes no warranties of any kind, expressed or implied, statutory or otherwise, and expressly disclaims all warranties of every kind, concerning the product, including warranties of merchantability or fitness for a particular purpose, except that this product should be capable of performing as described in each product's data sheet. KX Industries, L.P.'s obligation shall be limited solely to the refund of the purchase price or replacement of the product proven defective, at KX Industries, L.P.'s sole discretion. Determination of suitability of the product for uses and applications contemplated by Buyer shall be the sole responsibility of Buyer. Use of this product constitutes Buyer's acceptance of this Limited Liability.

269 South Lambert Road
Orange, CT 06477-3502
Telephone: 203-799-9000
Fax: 203-799-7000
Toll Free: 800-462-8745
E-mail: sales@kxindustries.com
www.kxindustries.com



This product is covered by one or more of the following United States Patent Nos. 5,019,311; 5,147,722; 5,189,092; 5,249,948; 5,331,037; 5,685,981; 5,922,803; 5,946,342; 6,061,384; 6,395,190; applicable foreign equivalents; and patents pending.

©2004 KX Industries, L.P. All rights reserved. KX, the KX logo, MATRIKX, the MATRIKX GENUINE EXTRUDED CARBON seal, MATRIKX + CTO, and CTO, are registered trademarks of KX Industries, L.P.